



Characteristics

Low initial tack, full adhesion achieved after 24 hours.

Print 6-8 months preservable.

Suitable for frozen food packaging as long as processed above 0°C.

Data	
Adhesion	Low initial tack, full adhesion achieved after 24 hours
Sound	Low-noise
Warranty	positive printing 6 months
Max. width printing	Tape width minus 2 mm
Colours	Clear, white, brown
Number of colours printed	Up to 5 colours
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	4 boxes = 144 rolls

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours	Thickness foil	
PPA	-	-	-	19	25	-	38	50	75	-	150		990 mtr	5	35 μ

Application

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Acrylic water-based
Elongation		150% \pm 10%
Thickness	mm	65 μ \pm 10%
Adhesion to steel	2,6 N/cm	\pm 10%
Tensile strenght	55 N/cm	\pm 10%

Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial